

ATLAS

STAINLESS STEEL FARMHOUSE SINK

SKU: 944665, 944662, 944658, 944653, 944661, 944664, 944649, 944648, 944663, 944638, 944668, 944666, 944655, 944650, 944651, 944656, 944647, 944659, 944639, 944667, 944654, 944660, 944640, 944637, 944652, 944657, 944646, 944645

BEFORE YOU BEGIN

We recommend consulting a professional if you are unfamiliar with installing plumbing fixtures. Signature Hardware accepts no liability for any damage to the plumbing, sink, counter top, or for personal injury during installation.

Observe all local plumbing and building codes.

Unpack and inspect the faucet for shipping damage. If any damage is found, contact our Customer Relations team at 1-866-855-2284.

GETTING STARTED

- Ensure that you have gathered all the required materials that are needed for the installation.

MATERIAL DESCRIPTION AND CARE

Stainless steel sinks are handcrafted from heavy gauge stainless steel, which is extremely durable, but can be scratched or scuffed when not cared for properly.


To maintain the condition of your stainless steel sink, simply clean daily with mild soap and warm water and wipe the entire surface dry with a dry, clean, soft cloth after each use. Keep sink free of any standing water to prevent the buildup of mineral deposits that can affect the appearance of your sink. Because iron particles often develop rust spots in stainless steel surfaces, do not leave steel cookware or utensils on the surface of the sink for long periods of time.

Do not use cleaners containing acids, harsh chemicals, or abrasives. Use the Stainless Steel Scratch-B-Gone Kit to remove minor scratches and maintain the beauty of your stainless steel fixture.

TOOLS AND MATERIALS:



Safety Glasses



Framing Square



Pencil



Tape Measure



Level



Hacksaw



Thread Sealant



Wood Shims



Basin Wrench



Drill

****Sealant - We recommend the use of neutral cure silicone caulk or a general purpose silicone sealant.**

REVISED 05/29/2020

CODES: 503296, 506668, 506665, 503293, 514413, 514415, 506666, 514403, 506667, 514418, 514411, 514412, 514420, 514404, 514419, 503295, 514428, 514416, 503316, 514402, 514426, 514423, 514417, 514414, 514422, 514425, 514410, 514405, 514424, 503294, 514429, 514427, 530321

For Warranty information, please visit: signaturehardware.com/services/warranty

ATLAS




STAINLESS STEEL FARMHOUSE SINK

SKU: 944665, 944662, 944658, 944653, 944661, 944664, 944649, 944648, 944663, 944638, 944668, 944666, 944655, 944650, 944651, 944656, 944647, 944659, 944639, 944667, 944654, 944660, 944640, 944637, 944652, 944657, 944646, 944645

INSTALLATION OPTIONS

We recommend undermount sink installation. Flush-mount and built-up installation are not recommended.

Ensure there is adequate room for the faucet and backsplash installations.



DRAIN INSTALLATION

Apply a bead of silicone sealant to the base of the strainer flange and place the flange in the drain opening in the sink.

If your drain has a disposer flange, use the directions supplied with the garbage disposer to attach the disposer and complete your installation. For drains with strainer baskets, slide the rubber gasket and friction washer up the strainer flange to the bottom of the sink.

Thread the lock nut onto the drain assembly. Hand-tighten and make sure that the drain is properly aligned. When ready, finish tightening with a basin wrench to secure the drain. Secure the P-trap to the strainer flange with the provided compression nut and ferrule.

ATLAS

STAINLESS STEEL FARMHOUSE SINK


SKU: 944665, 944662, 944658, 944653, 944661, 944664, 944649, 944648, 944663, 944638, 944668, 944666, 944655, 944650, 944651, 944656, 944647, 944659, 944639, 944667, 944654, 944660, 944640, 944637, 944652, 944657, 944646, 944645

PREPARE THE CABINET

Farmhouse sinks may require custom cabinetry. We recommend consulting an experienced cabinet maker for assistance. Providing the cabinet maker with the actual sink that is to be installed will ensure a custom fit.


Allow clearance for the water supply lines, drains and a garbage disposal, if applicable. Build a support frame or install support bars from front to back along the inner sides of the cabinet. The frame must support the weight of the sink and all attachments.

The support frame should be positioned so that when installed, the sink is in line and level with the top of the cabinet.



TEMPLATE AND CUTOUT

No template is provided since each sink will vary dimensionally. After centering the sink, trace the outline of the sink on the counter-top with a pencil to use as a guide for the cutout. Remember to allow clearance for any faucets and/or backsplashes. Cut the counter-top accordingly.



FINAL PLACEMENT

Test fit the sink in the opening that was created in the previous steps. The entire weight of the sink should be supported by the support frame. Verify that the sink is in line and level with the top of the cabinet. Use shims, if needed, to level the sink.

Set the sink and apply your sealant to fill in any gaps below the sink front, and between the sink and counter-top. Hold the sink in place to secure. Place the counter-top onto the sink and remove any excess sealant from all surfaces.

