



# CAST IRON DROP-IN SINK

## BEFORE INSTALLING

Read entire Drop-In Sink Installation Instructions. Observe all local building and safety codes.

## INSTRUCTIONS

For this installation it is assumed that the countertop has been cut to the dimensions of the sink. We recommend consulting a professional if you are unfamiliar with this type of installation. Signature Hardware accepts no liability for any damages to the floor, walls, plumbing or for personal injury during installation.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-866-855-2284. If you need assistance or have questions while installing your sink, contact Customer Service.

## TOOLS AND MATERIALS:



Level



Silicone Sealant



Damp Cloth



Basin Wrench



Thread Sealant

## MATERIAL DESCRIPTION AND CARE

Cast iron sinks are extremely durable and beautifully finished with a thick enamel top layer. The enamel coating creates a beautiful glossy sheen and is nonporous, which prevents rust, tarnish, and allows for thorough cleaning. The enamel finish prevents corrosion and acid, which helps to keep your sink looking new and performing well over time.

Cleaning and maintenance are easy. A thorough rinsing and wipe-down with a soft cloth is recommended after each use.

## INSTALLATION

1. Lower the sink into the sink cutout on the counter to confirm the sink will fit properly. The perimeter of the sink rim should connect with the counter while the sink bowl should sit completely inside the counter.

**Tip: For easier installation, install the drain and faucet before attaching the sink to the counter.**

2. Remove the sink and run a bead of silicone sealant around the sink cutout to seal the rim against moisture and leaks.

3. Carefully lower the sink back into the cutout and press the sink firmly into the sealant. Make sure that the sink is level and properly aligned.

4. With the sink in place, tighten the mounting clips (if included) on the underside of the sink.

5. Wipe away any excess sealant around the rim of the sink with a damp cloth